

HYDROIL serie NS

Struttura, coperchio, cestello e porta-cesto in acciaio inox AISI 304.

Basamento in ferro zincato (a richiesta in acciaio inox)

Motore elettrico autofrenante, protezione IP55, di nostra produzione, montato su tassello ammortizzante, idoneo ad assorbire forti sollecitazioni.

Blocco coperchio di sicurezza.

Consolle comandi in bassa tensione v.24 ; quadro elettrico racchiuso in cassetta inox a bordo macchina.

Stainless steel 304 structure, cover, basket and basket stand.

Galvanizing iron base (stainless steel on request).

Electrical motor IP55 protection, assembled on a special rubber absorbing screw to deaden strong stress.

Frontal safety cap's lock.

Low tension 24v for control console; electric board contained in a stainless steel box.



Centrifuga disoliatrice con quadro comandi installato a bordo macchina Centrifuge for oil separation with electric control panel on board machine



SERIE OIL NS	CAPACITA' CESTO BASKET CAPACITY		KW	GIRI RPM	Misure CESTO BASKET Dimension Ø x H	VOLTAGGIO TENSION		
	KG	LT				Monofase Single-phase	Trifase Three-phase	
HYDROIL NS	88	30	32	0,8	700	408 X 245	V.230 Hz 50	V.400 Hz 50
HYDROIL NS R	88	15	19,5	0,8	1400	318 X 245	V.230 Hz 50	V.400 Hz 50
HYDROIL NS	128	50	52	1,6	700	480 X 285		V.400 Hz 50
HYDROIL NS R	128	25	32	1,6	1400	408 X 245		V.400 Hz 50
HYDROIL NS	328	80	72	2,3	700	480 X 400		V.400 Hz 50
HYDROIL NS	528	95	85	3,5	700	550 X 400		V.400 Hz 50

Rumorosità – Noise = < 70 DB (A)

Possibilità di voltaggi speciali su richiesta - Special voltage on request