

# HYDROIL serie NS

Struttura, coperchio, cestello e porta-cesto in acciaio inox AISI 304.

Basamento in ferro zincato ( a richiesta in acciaio inox )

Motore elettrico autofrenante, protezione IP55, di nostra produzione, montato su tassello ammortizzante, idoneo ad assorbire forti sollecitazioni.

Blocco coperchio di sicurezza.

Consolle comandi in bassa tensione v.24 ; quadro elettrico racchiuso in cassetta inox a bordo macchina.

Stainless steel 304 structure, cover, basket and basket stand.

Galvanizing iron base ( stainless steel on request ).

Electrical motor IP55 protection, assembled on a special rubber absorbing screw to deaden strong stress.

Frontal safety cap's lock.

Low tension 24v for control console; electric board contained in a stainless steel box.



## Centrifuga disoliatrice con quadro comandi installato a bordo macchina Centrifuge for oil separation with electric control panel on board machine



SERIE OIL NS	CAPACITA' CESTO BASKET CAPACITY		KW	GIRI RPM	Misure CESTO BASKET Dimension Ø x H	VOLTAGGIO TENSION		
	KG	LT				Monofase Single-phase	Trifase Three-phase	
HYDROIL NS	88	30	32	0,8	700	408 X 245	V.230 Hz 50	V.400 Hz 50
HYDROIL NS R	88	15	19,5	0,8	1400	318 X 245	V.230 Hz 50	V.400 Hz 50
HYDROIL NS	128	50	52	1,6	700	480 X 285		V.400 Hz 50
HYDROIL NS R	128	25	32	1,6	1400	408 X 245		V.400 Hz 50
HYDROIL NS	328	80	72	2,3	700	480 X 400		V.400 Hz 50
HYDROIL NS	528	95	85	3,5	700	550 X 400		V.400 Hz 50

Rumorosità – Noise = < 70 DB (A)

Possibilità di voltaggi speciali su richiesta - Special voltage on request