

HYDROMETAL serie NS

Struttura, coperchio, cestello e porta-cesto in acciaio inox AISI 304.

Basamento in ferro zincato (a richiesta in acciaio inox)

Motore elettrico autofrenante, protezione IP55, di nostra produzione, montato su tassello ammortizzante, idoneo ad assorbire forti sollecitazioni.

Resistenza e vano porta resistenza inox 18/8 con griglia di protezione.

Blocco coperchio di sicurezza.

Consolle comandi in bassa tensione v.24 ; quadro elettrico racchiuso in cassetta inox a bordo macchina.

Stainless steel 304 structure, cover, basket and basket stand.

Galvanizing iron base (stainless steel on request).

Electrical motor IP55 protection, assembled on a special rubber absorbing screw to deaden strong stress.

Resistance and resistance holder in stainless steel 18/8 with protective grill.

Frontal safety cap's lock.

Low tension 24v for control console; electric board contained in a stainless steel box.



Essicatore Centrifuga con quadro comandi installato a bordo macchina Drier Centrifugal with electric control panel on board machine



SERIE NS	CAPACITA' CESTO BASKET CAPACITY		KW	GIRI RPM	Misure CESTO BASKET Dimension Ø x H	RESISTENZA RESISTANCE KW	VOLTAGGIO TENSION	
	KG	LT					Monofase Single-phase	Trifase Three-phase
HYDROMETAL NS 68	20	19.5	0.6	700	318 x 245	1.3	V.230 Hz 50	V.400 Hz 50
HYDROMETAL NS 88	30	32	0.8	700	408 x 245	1.8	V.230 Hz 50	V.400 Hz 50
HYDROMETAL NS 128	50	52	1.6	700	480 x 285	1.8		V.400 Hz 50
HYDROMETAL NS 228	65	72	2.3	700	480 x 400	2.2		V.400 Hz 50
HYDROMETAL NS 328	80	72	2.3	700	480 x 400	3		V.400 Hz 50
HYDROMETAL NS 528	95	85	3.5	700	550 x 400	3		V.400 Hz 50

Rumorosità – Noise = < 70 DB (A)

Possibilità di voltaggi speciali su richiesta - Special voltage on request